



The CheatSheet – CakePHP 1.2

Config

Core

```

debug
App.encoding
App.baseUrl
App.dir
Cache.check
Cache.disable
Acl.className
Acl.database
Routing.admin
Session.start
Session.save
Session.checkAgent
Session.cookie
Session.timeout
Security.level
Security.salt
Asset.filter.js
Asset.filter.css

```

Index.php

```

CAKE_CORE_INCLUDE_PATH
ROOT
WWW_ROOT
WEBROOT_DIR

```

Paths

```

APP
APP_DIR
APP_PATH
CACHE
CAKE
COMPONENTS
CONFIGS
CONTROLLER_TESTS
CONTROLLERS
CSS
ELEMENTS
HELPER_TESTS
HELPERS
INFLECTIONS
JS
LAYOUTS
LIB_TESTS
LIBS
LOGS
MODEL_TESTS
MODELS
TESTS
TMP
VENDORS
VIEWS

```

Model

Properties

```

$cacheQueries
$data
$displayField
$id
$name
$primaryKey

```

```

$recursive
$dbConfig
$useTable
$validate
$validationErrors
$schema

```

Relationships

```

$belongsTo
$hasAndBelongsToMany
$hasMany
$hasOne

```

Methods

```

bind(params)
create([data])
delete([id, cascade])
deleteAll(conditions, [cascade, callbacks])
escapeField(field)
exists()
field(name, conditions, order)
find(type, [options])
getAffectedRows()
getAssociated([type])
getColumnType(column)
getInsertID()
getNumRows()
hasAny([conditions])
hasField(name)
invalidate(field)
invalidFields([data])
isForeignKey(field)
isUnique(fields, [or])
query([sql])
read([fields, id])
save([data, options])
saveAll([data, options])
saveField([name, value, validate])
schema([field])
set(one, [two])
setDataSource(dataSource)
setSource(tableName)
unbindModel(params, [reset])
updateAll(fields, [conditions])
updateCounterCache([keys, created])
validates([options])

```

Custom Find Types: all, first, count, list, threaded, neighbors

Callbacks

```

beforeDelete()
afterDelete()
beforeFind(query)
afterFind(results, primary)
beforeValidate()
beforeSave()
afterSave()

```

Global Functions

```

config('fileName')
debug(message, [escape])
pr(string | array | object)
e(message)
h(string | array)
am(array, [array, array])
cache(path, data, expires, [target])
clearCache([params, type, ext])
env('HTTP_HEADER')
__(singular, [return])
__n(singular, plural, count, [return])
__d(domain, msg, [return])
__dn(domain, singular, plural, count, [return])
__dc(domain, msg, category, [return])
__dcn(domain, singular, plural, count, category, [return])
__c(msg, category, [return])

```

Controller

Properties

```

$name
$action
$autoLayout
$autoRender
$base
$cacheAction
$components
$data
$helpers
$here
$layout
$output
$pageTitle
$params
$persistModel
$plugin
$uses
$view
$viewPath
$webroot

```

Methods

```

constructClasses()
header(status)
paginate ([object, scope, whitelist])
disableCache()
postConditions(data)
redirect(url, [status])
referer([default, local])
render([action, layout, le])
set(one, [two])
setAction (action, [param, param, param])
validate()
validateErrors()

```

Callbacks

```

beforeFilter()
beforeRender()
afterFilter()

```

Component

Properties

```
$enabled
```

Callbacks

```

initialize(&controller)
startup(&controller)
beforeRender(&controller)
beforeRedirect(&controller)
shutdown(&controller)

```

View

Properties

```

$action
$autoLayout
$autoRender
$base
$ext
$hasRendered
$helpers
$here
$layout
$loaded
$model
$name
$pageTitle
$params
$plugin
$subDir
$themeWeb
$uses
$viewPath

```

Methods

```

addScript (name, [content])
element (name, [params, loadHelpers])
error (code, name, message)
getVar (var)
getVars ( )
renderCache ( lename, timeStart)
render ([action, layout, le])
renderLayout(content, [layout])
set (one, [tset (one, [two])])

```

Helper

Properties

```

$base
$here
$action
$themeWeb
$view
$webroot
$params
$data
$plugin

```

Methods

```

url([url, full])
webroot(file)
clean(text)
value([field/options, field, key])

```

Callbacks

```

afterRender()
beforeLayout()
afterLayout()

```

Models Conventions

Class: singular, camel cased (LineItem, Person)

File: singular, underscored (line_item.php, person.php)

Table: plural, underscored (line_items, people)

Controllers

Class: plural, camel cased, ends in "Controller" (LineItemsController, PeopleController)

File: plural, underscored (line_items_controller.php, people_controller.php)

Views

Path: controller name, underscored (app/views/line_items/<file>, app/views/people/<file>)

File: action name, underscored (index.ctp, view.ctp, admin_index.ctp)